

Rittal – The System.

Faster – better – everywhere.

NH fuse-switch- disconnectors, size 00 to 3 – SV 9343.100

Date : Jun 20, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



NH fuse-switch-disconnectors, size 00 to 3 – SV

9343.100

created: 20.06.2017 on www.rittal.com/com-en



Product description

Material: Polyamide (PA 6)
Fire protection corresponding to UL 94-V0
Contact tracks: Electrolytic copper, silver-plated

Colour: Chassis: RAL 7035
Cover: RAL 7035/7001

Basis of test: IEC/DIN EN 60 947-3
DIN EN 60 269-2 (fuse inserts)

Note: The technical data may vary for UR applications. Applications to UR only in conjunction with "Special Purpose Fuses".

Product features

Design: Size: 1

To fit busbars: with cross-section height: 5 mm
with cross-section height: 10 mm

Number of poles: 3-pole

For bar systems with centre-to-centre spacing: 60 mm

Dimensions: Width: 184 mm
Height: 298 mm

Type of electrical connection:	Box terminal
Rated operating voltage:	690 V, 3~
Clamping area for laminated copper bars:	Width: 20 mm Height: 3 mm Height: 14 mm
Connection for round conductor cross-sections:	35 mm ² - 150 mm ² Note: Connection of sector-shaped conductors 50 – 150 mm ² .
Rated operating current max.:	250 A
Cable outlet:	Top/bottom
Packs of:	1 pc(s).
Weight/pack:	2.34 kg
EAN:	4028177540323
Customs tariff number:	85369095
ETIM 6.0:	EC001040
ETIM 5.0:	EC001040
eCl@ss 8.0/8.1:	27371401
eCl@ss 7.0/7.1:	27371401
eCl@ss 6.0/6.1:	27371401
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV NH fuse-switch disconnecter, size 1, 250 A, 690 V, 3-pole, box terminal
Approvals	
Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity

